



Quantum

Quantum Bus & Van Specifications

	2.8 LWB P / Van 3s w/AC	2.8 SLWB P / Van 3s w/AC	2.8 LWB Crew Cab 6s w/AC	2.8 GL Bus 11s	2.8 GL Bus 14s
Engine and Drivetrain					
Maximum Power (kW @ r/min)	130 @ 3400	130 @ 3400	130 @ 3400	130 @ 3400	115 @ 3600
Maximum Torque (Nm @ r/min)	420 @ 1400-2600	420 @ 1400-2600	420 @ 1400-2600	420 @ 1400-2600	420 @ 1600-2200
Transmission	6-speed MT	6-speed MT	6-speed MT	6-speed MT	6-speed MT
Starting System	Rotary (Mechanical)	Rotary (Mechanical)	Rotary (Mechanical)	Rotary (Mechanical)	Rotary (Mechanical)
Driven Wheels	RWD	RWD	RWD	RWD	RWD
Bore x Stroke (mm)	92.0 x 103.6	92.0 x 103.6	92.0 x 103.6	92.0 x 103.6	92.0 x 103.6
Fuel System	Diesel	Diesel	Diesel	Diesel	Diesel
Turbo Charger					
Suspension					
Front	MacPherson	MacPherson	MacPherson	MacPherson	MacPherson
Rear	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring
Wheels and Tyres					
Tyre Size	215 / 70-R16C Steel	215 / 70-R16C Steel	215 / 70-R16C Steel	235 / 65-R16C Alloy	235 / 65-R16C Alloy
Spare Wheel					
Body and Styling					
Front Bumper	Black	Black	Black	Painted	Painted
Rear Bumper	Black	Black	Black	Painted	Painted
ront Grille	Colour	Colour	Colour	Chrome	Chrome
Door Outside Handles	Black	Black	Black	Colour-Coded	Colour-Coded
leadlights	Halogen	Halogen	Halogen	Halogen	Halogen
Daytime Running Lights (DRL)	Bulb	Bulb	Bulb	LED	LED
leadlamp Levelling	•	•	•	•	
Rear Lights (Bulb Type)					
Front & Rear Fog Lamps	Rear Only	Rear Only	Rear Only		
				Colour-Coded /	Colour-Coded /
Side Mirrors	Black / Retractable	Black / Retractable	Black / Retractable	Power Retractable / Power	Power Retractable / Pow
ight Control System		•	•		•
nterior, Comfort and Convenience					
upholders					
ear View Mirror	Electrochromatic	Electrochromatic	Electrochromatic	Electrochromatic	Electrochromatic
everse Camera In Rear View Mirror					
lverhead Console					
nd Row Seats			Fixed	Fixed	Fixed
ront Seat Adjustment / Reclining	•				
ront Seat Vertical Adjuster	Driver / Manual	Driver / Manual	Driver / Manual	Driver / Manual	Driver / Manual
eat Trim	Fabric	Fabric	Fabric	Fabric	Fabric
ir Conditioner					
lulti-Information Display (MID)					
ower Socket	Front - 12V x2	Front - 12V x2	Front - 12V x2	Front - 12V x2 /	Front - 12V x2 /
				Rear USB Charging x2	Rear USB Charging x2
teering Wheel	4 Spoke / Urethane	4 Spoke / Urethane	4 Spoke / Urethane	4 Spoke / Urethane	4 Spoke / Urethane
teering Column Adjustments	Manual / Tilt & Telescopic	Manual / Tilt & Telescopic	Manual / Tilt & Telescopic	Manual / Tilt & Telescopic	Manual / Tilt & Telescopio
ower Steering	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
lectric Windows	Front / One Touch Driver & Passener Only	Front / One Touch Driver & Passener Only	Front / One Touch Driver & Passener Only	Front / One Touch Driver & Passener Only	Front / One Touch Driver & Passener Only
Steering Switches	Audio / Telephone	Audio / Telephone	Audio / Telephone	Audio / Telephone	Audio / Telephone
udio System	•		•	•	•
Bluetooth / AUX / USB					
Speakers	2	2	2	6	6
					-

	2.8 LWB P / Van 3s w/AC	2.8 SLWB P / Van 3s w/AC	2.8 LWB Crew Cab 6s w/AC	2.8 GL Bus 11s	2.8 GL Bus 14s
Safety and Security					
Anti-theft System	Immobiliser / Alarm	Immobiliser / Alarm	Immobiliser / Alarm	Immobiliser / Alarm	Immobiliser / Alarm
Power Door Lock					
Child Restraint System (ISOFIX)			2		
Driver and Front Passenger Airbags		•	•	•	•
Wireless Door Lock	•	•	•	•	•
Driver Support Systems					
Anti-Lock Braking System (ABS)		•	•	•	•
Brake-Assist (BA)	•	•	•	•	•
Hill-Assist Control (HAC)	•	•	•	•	•
Vehicle-Stability Control (VSC)	•	•	•	•	•
Trailer Sway Control (TSC)	•	•	•	•	•
Dimensions and Capacities					
Height (mm)	1990	2280	1990	1990	2280
Length (mm)	5265	5915	5265	5265	5915
Width (mm)	1950	1950	1950	1950	1950
Wheelbase (mm)	3210	3860	3210	3210	3860
Fuel Tank Size (∕)	70	70	70	70	70
Gross Combination Mass (GCM)	5200	4900	5200	4945	5310
Gross Vehicle Mass (GVM)	3300	3500	3300	3445	3810
Towing Capacity - Unbraked (kg)	400	400	400	400	400
Towing Capacity - Braked (kg)	1900	1400	1900	1500	1500
Approach Angle (°)	15.2	15.2	15.2	15.2	15.2
Departure Angle (°)	15.4	15.4	15.4	15.4	15.4
Service and Warranty plan					
Service Interval	12 months / 10 000 k	m 12 months / 10 000 k	m 12 months / 10 000 km	12 months / 10 000 km	12 months / 10 000 km
Service Plan	9 services / 90 000 F	km 9 services / 90 000 k	9 services / 90 000 km	9 services / 90 000 km	9 services / 90 000 km
Warranty	3 years / 100 000 kr	m 3 years / 100 000 kr	m 3 years / 100 000 km	3 years / 100 000 km	3 years / 100 000 km

COLOUR SWATCHES





Ivory White 058

Quicksilver Metallic 1E7*

*Customer order only

**Customer order only for GL Bus

DISCLAIMER:

The information contained in this leaflet is provided as is and without any warranties of any kind, whether expressed or implied, including but not limited to, implied warranties of satisfactory quality, fitness for a particular purpose and/or correctness. The contents of this leaflet are for general information purposes only and do not constitute advice. Toyota Motor Corporation of Japan and Toyota South Africa Motors (Pty) Limited does not represent or warrant that the information and/or specifications contained in this leaflet are accurate, complete or current and specifically stipulates that certain vehicle details and specifications contained in this leaflet may differ in available models. Therefore, neither Toyota Motor Corporation of Japan nor Toyota South Africa Motors (Pty) Limited make any warranties or representations regarding the use of the content, details, specifications, or information contained in this leaflet in terms of their correctness, accuracy, adequacy, usefulness, timeliness, reliability or otherwise, in each case to the fullest extent permitted by law. Please note that claiming of input VAT needs to be verified by customers prior to vehicle purchase as these rulings are subject to SARS interpretation. Toyota South Africa Motors' rights remain reserved.

